

Product Specification		Units	GHR-10/058	GHR-10/060
Contact Form			C	C
Contact Arrangement			SPDT	SPDT
Test Voltage,(kV, Peak), Test Max.,Contacts & to Base (15 μ A Leakage Max., dc or 60Hz)		KV Peak	20	20
Rated Operating Voltage,(kV, Peak), Contacts & to Base (15 μ A Leakage Max.)	DC or 60Hz	KV Peak	15	15
	2.5MHz	KV Peak	-	13
	16MHz	KV Peak	-	10
	32MHz	KV Peak	-	-
Continuous Current,Carry Max	DC or 60Hz	Amps	50	75
	2.5MHz	Amps	-	35
	16MHz	Amps	-	22
	32MHz	Amps	-	-
Coil Hi -Pot (V RMS, 60 Hz)		V	500	500
Capacitance	Across Open Contacts	pF	3	3
	Contacts to Ground	pF	3.5	3.5
Resistance, Contact Max @ 1A, 28Vdc		Ω	0.025	0.01
Operate Time, Max		ms	30	30
Release Time, Max		ms	8	8
Operating Temperature Ambient		$^{\circ}$ C	-55~+125	-55~+125
Shock, 1/2 Sine11ms (Peak)		G' s	50	50
Vibration, Sine (10-2000 Hz Peak)		G' s	10	10
Mechanical Life		Cycles	1 million	1 million
Weight		g	290	290

COIL RATINGS	
Nominal, Volts dc	24
Pick-up, Volts dc,Max	16
Drop-Out, Volts dc,Min	3.5
Coil Resistance ($\Omega \pm 10\%$)	190
※ Ratings listed are for 25°C, sea level conditions	

※ Order the relay with the coil voltage in the part number as shown above. The coil voltage will appear on the coil plate near the coil terminals rather than in the P/N on the relay.

