

Product Specification		Units	GHR-61-SP
Contact Form			C
Contact Arrangement			SPDT
Test Voltage,(kV, Peak), Test Max.,Contacts & to Base (15 μ A Leakage Max., dc or 60Hz)		KV Peak	40
Rated Operating Voltage,(kV, Peak), Contacts & to Base (15 μ A Leakage Max.)	DC or 60Hz	KV Peak	35
	2.5MHz	KV Peak	29
	16MHz	KV Peak	21
	32MHz	KV Peak	-
Continuous Current,Carry Max	DC or 60Hz	Amps	20
	2.5MHz	Amps	12
	16MHz	Amps	7
	32MHz	Amps	-
Coil Hi -Pot (V RMS, 60 Hz)		V	500
Capacitance	Across Open Contacts	pF	0.5
	Contacts to Ground	pF	1
Resistance, Contact Max @ 1A, 28Vdc		Ω	0.05
Operate Time, Max		ms	18
Release Time, Max		ms	18
Operating Temperature Ambient		$^{\circ}$ C	-55~+125
Shock, 1/2 Sine11ms (Peak)		G' s	50
Vibration, Sine (10-2000 Hz Peak)		G' s	10
Mechanical Life		Cycles	1 million
Weight		g	230

COIL RATINGS			
Nominal, Volts dc	26.5	24	12
Pick-up, Volts dc,Max	18	18	9
Drop-Out, Volts dc,Min	1-10	1-10	0.5-5
Coil Resistance ($\Omega \pm 10\%$)	125	125	30
※ Ratings listed are for 25°C, sea level conditions			

※ Order the relay with the coil voltage in the part number as shown above. The coil voltage will appear on the coil plate near the coil terminals rather than in the P/N on the relay.

